

## ***Especificaciones Técnicas***

### **ENCINTADORA SEMI AUTOMÁTICA JOINPACK JP501**

#### **Para cajas de tamaño uniforme**

**(SKU Empack 14049)**

Ancho de cinta: 2" ó 3"

(customizable, se debe especificar al momento de la compra)

Tamaño de sellado:

2" tape: L150~∞ x W110~500xH110~500mm

3" tape: L150~∞x W135~500x H110~500mm

Energía:

Monofásica 110/220/240V,50/60Hz

Trifásica 380/415/440V,50/60Hz

(customizable, se debe especificar al momento de la compra)

Velocidad de la banda: 20 M / por minuto (60 Hz)

Altura de la mesa: H 570 ~ 770 mm

Tamaño de la máquina: L 1250 x W 960 x H 1420 mm

Garantía: 6 meses



## JP-501

**Tape Sealing, Side Belt Driven**

### Description

Manually adjust width & height by two handles to cope with variety of boxes. Reliable taping heads apply tapes smoothly. Side belt driven is suitable for narrow box.

### Features

- For uniform box
- Side belt driven
- Sturdy mast & frame
- Taping heads seal box smooth & accurate
- Dual side wheels help box close while taping
- Table height adjustable from 570~770 mm

### Options

- Extension roller table
- Stainless steel housing #304
- Width & height increase in size
- For heavy load, choose upper and side belt driven, JP-501T

### Specification

|                                |                                                                                     |
|--------------------------------|-------------------------------------------------------------------------------------|
| Sealing size (L x W x Hmm)     | Max. ∞ x 500 x 500<br>Min. 150 x 110 x 110 for 2"tape<br>150 x 135 x 110 for 3"tape |
| Tape width                     | 2" or 3" (specified)                                                                |
| Table height (mm)              | 570~700                                                                             |
| Belt speed                     | 20 M/per min. at 60Hz                                                               |
| Power supply                   | 110/220/230/240V, 50/60Hz, 1PH<br>220/230/380/415/440V, 50/60Hz, 3PH                |
| Layout dimension (L x W x Hmm) | 1250 x 960 x 1420                                                                   |

\*Specification subject to change without notice